

SAFETY DATA SHEET

1. Identification

Product identifier **662 STINGER® LEATHER & VINYL DYE (DARK TAN)**

Product Code 662

Recommended use Not available.

Manufacturer/Importer/Supplier/Distributor

Company name Stinger Chemical, LLC
905 Live Oak Street
Address Houston, Texas 77003
United States
Telephone 713-227-1340
Website www.stingerchemicals.com

Emergency phone number CHEMTREC 1-800-422-9300 (USA)
CANUTEC 1-613-996-6666 (CANADA)

2. Hazard(s) identification

hazards	Flammable aerosols	Gases under pressure	
	Skin corrosion/irritation		Category 1
	Serious eye damage/eye irritation	Carcinogenicity	Liquefied gas
	Reproductive toxicity		Category 2
	Specific target organ toxicity, single exposure		Category 2A
	Specific target organ toxicity, repeated exposure		Category 2
	Hazardous to the aquatic environment, acute hazard		Category 1
Environmental hazards	Hazardous to the aquatic environment, long-term hazard		Category 3 narcotic effects
			Category 1
	Not classified.		

OSHA defined hazards Category 2

Label elements Category 3



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information 43.59% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 43.59% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ACETONE N-		67-64-1	40 to <50
BUTANE		106-97-8	10 to <20
PROPANE		74-98-6	10 to <20
TOLUENE		108-88-3	10 to <20
METHYL ETHYL KETONE		78-93-3	1 to <5
PROPYLENE GLYCOL METHYL ETHER ACETATE		108-65-6	1 to <5
TITANIUM DIOXIDE XYLENE		13463-67-7	1 to <5
1-METHYL-2-PYRROLIDONE BUTYL BENZYL		1330-20-7	1 to <5
PHthalate ETHYLBENZENE		872-50-4	0.1 to <1
		85-68-7	0.1 to <1
		100-41-4	0.1 to <1
Other components below reportable levels			5 to <10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact No adverse effects due to skin contact are expected. Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. No specific first aid measures noted.

Ingestion Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Secure cylinders in an upright position at all times, close all valves when not in use. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm	
ETHYLBENZENE (CAS 100-41-4)	PEL	435 mg/m ³ 100 ppm	
METHYL ETHYL KETONE (CAS 78-93-3)	PEL	590 mg/m ³ 200 ppm	
PROPANE (CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm	
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.
XYLENE (CAS 1330-20-7)	PEL	435 mg/m ³ 100 ppm	

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
TOLUENE (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
ACETONE (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	300 ppm
N-BUTANE (CAS 106-97-8)	TWA	200 ppm
	STEL	1000 ppm
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m ³
TOLUENE (CAS 108-88-3)	TWA	20 ppm
	STEL	150 ppm
XYLENE (CAS 1330-20-7)	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards Components

Components	Type	Value
ACETONE (CAS 67-64-1)	TWA	590 mg/m ³ 250 ppm
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m ³ 125 ppm
	TWA	435 mg/m ³
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	100 ppm 885 mg/m ³
		300 ppm
N-BUTANE (CAS 106-97-8)	TWA	590 mg/m ³
PROPANE (CAS 74-98-6)	TWA	200 ppm 1900 mg/m ³
TOLUENE (CAS 108-88-3)	TWA	800 ppm 1800 mg/m ³ 1000 ppm
	STEL	560 mg/m ³ 150 ppm

US. NIOSH: Pocket Guide to Chemical Hazards Components Type

Value
 100 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides Components Type

Value

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)	TWA	40 mg/m ³
PROPYLENE GLYCOL METHYL ETHER ACETATE (CAS 108-65-6)	TWA	10 ppm 50 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
1-METHYL-2-PYRROLIDONE (CAS 872-50-4)	100 mg/l	5-Hydroxy-N-methyl-2-pyrrolidone	Urine	*
ACETONE (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
METHYL ETHYL KETONE (CAS 78-93-3)	2 mg/l	MEK	Urine	*
TOLUENE (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
XYLENE (CAS 1330-20-7)	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

PROPYLENE GLYCOL METHYL ETHER ACETATE (CAS 108-65-6) Can be absorbed through the skin.
 TOLUENE (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

TOLUENE (CAS 108-88-3) Skin designation applies.

US WEEL Guides: Skin designation

1-METHYL-2-PYRROLIDONE (CAS 872-50-4) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
 Other Wear appropriate chemical resistant clothing.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol. Liquefied gas.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-305.68 °F (-187.6 °C) estimated
Initial boiling point and boiling range	-43.78 °F (-42.1 °C) estimated
Flash point	-156.0 °F (-104.4 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	1.3 % estimated
Flammability limit - upper (%)	12.8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	2304.83 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	550 °F (287.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.

Other information

Density	6.09 lbs/gal
Flammability class	Flammable IA estimated
Heat of combustion (NFPA 30B)	30 kJ/g estimated
Percent volatile	90.41
Specific gravity	0.73
VOC	348.119352 g/l Material 2.9051968 lbs/gal Material 4.8035687 lbs/gal Regulatory 575.594474 g/l Regulatory

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Narcotic effects.

Components **Species** **Test Results**

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)

Acute

Dermal

LD50 Rabbit 8000 mg/kg

Oral

LD50 Mouse 5130 mg/kg
 Rat 3914 mg/kg
 4.2 ml/kg

ACETONE (CAS 67-64-1)

Acute

Dermal

LD50 Rabbit > 15800 mg/kg

Inhalation

LC50 Rat 76 mg/l, 4 Hours

Oral

LD50 Mouse 3000 mg/kg
 Rat 5800 mg/kg

BUTYL BENZYL PHTHALATE (CAS 85-68-7)

Acute Dermal

LD50 Mouse 6700 mg/kg
 Rat 6700 mg/kg

Oral

ETHYLBENZENE (CAS 100-41-4)

LD50 Rat 13500 mg/kg

Acute

Dermal

LD50 Rabbit 17800 mg/kg

Oral

LD50 Rat 3500 mg/kg

METHYL ETHYL KETONE (CAS 78-93-3)

Acute Dermal

LD50 Rabbit > 8000 mg/kg

Inhalation

LC50 Mouse 11000 ppm, 45 Minutes
 Rat 11700 ppm, 4 Hours

Components	Species	Test Results
Oral		
LD50	Mouse	670 mg/kg
	Rat	2300 - 3500 mg/kg
N-BUTANE (CAS 106-97-8)		
Acute Inhalation		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
PROPANE (CAS 74-98-6)		
Acute Inhalation		
LC50	Rat	> 1442.847 mg/l, 15 Minutes
TOLUENE (CAS 108-88-3)		
Acute Dermal		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
XYLENE (CAS 1330-20-7)		
Acute Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

BUTYL BENZYL PHTHALATE (CAS 85-68-7)	3 Not classifiable as to carcinogenicity to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
TITANIUM DIOXIDE (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
TOLUENE (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.

XYLENE (CAS 1330-20-7)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not classifiable as a carcinogenic to humans.

Not listed.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. May damage fertility or the unborn child.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
ACETONE (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours 4740
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	- 6330 mg/l, 96 hours
BUTYL BENZYL PHTHALATE (CAS 85-68-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 0.96 mg/l, 48 hours
Fish	LC50	Shiner perch (Cymatogaster aggregata)	0.47 - 0.56 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
METHYL ETHYL KETONE (CAS 78-93-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	4025 - 6440 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	> 400 mg/l, 96 hours
TITANIUM DIOXIDE (CAS 13463-67-7)			
Aquatic			
Crustacea Fish	EC50	Water flea (Daphnia magna) Mummichog	> 1000 mg/l, 48 hours
TOLUENE (CAS 108-88-3)	LC50	(Fundulus heteroclitus)	> 1000 mg/l, 96 hours
Aquatic Crustacea			
Fish	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
XYLENE (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow) -0.54

1-METHYL-2-PYRROLIDONE

ACETONE -0.24

Partition coefficient n-octanol / water (log Kow)

BUTYL BENZYL PHTHALATE	4.91
ETHYLBENZENE	3.15
METHYL ETHYL KETONE	0.29
N-BUTANE	2.89
PROPANE	2.36
TOLUENE	2.73
XYLENE	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950
UN proper shipping name Transport Aerosols, flammable, 2.1
hazard class(es) Not available.
Class Subsidiary -
risk Not applicable.
Packing group
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1950
UN proper shipping name Transport Aerosols, flammable, 2.1
hazard class(es) Not available.
Class Subsidiary -
risk Not applicable.
Packing group Environmental hazards No.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Forbidden. Forbidden.
Cargo aircraft only

IMDG

UN number UN1950
UN proper shipping name Transport Aerosols, flammable, 2.1
hazard class(es) Not available.
Class Subsidiary -
risk Not applicable.
Packing group Environmental hazards No.
Marine pollutant EmS Not available.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

BUTYL BENZYL PHTHALATE (CAS 85-68-7) Phthalates Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

ACETONE (CAS 67-64-1) Listed.
BUTYL BENZYL PHTHALATE (CAS 85-68-7) Listed.
ETHYLBENZENE (CAS 100-41-4) Listed.
METHYL ETHYL KETONE (CAS 78-93-3) Listed.
N-BUTANE (CAS 106-97-8) Listed.
PROPANE (CAS 74-98-6) Listed.
TOLUENE (CAS 108-88-3) Listed.
XYLENE (CAS 1330-20-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes Pressure
Hazard - No Reactivity Hazard -
No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
TOLUENE	108-88-3	10 to <20
XYLENE	1330-20-7	1 to <5
1-METHYL-2-PYRROLIDONE	872-50-4	0.1 to <1
ETHYLBENZENE	100-41-4	0.1 to <1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYLBENZENE (CAS 100-41-4)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

N-BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

ACETONE (CAS 67-64-1) 6532
METHYL ETHYL KETONE (CAS 78-93-3) 6714
TOLUENE (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

ACETONE (CAS 67-64-1) 35 %W

METHYL ETHYL KETONE (CAS 78-93-3)	35 %wv
TOLUENE (CAS 108-88-3)	35 %wv
DEA Exempt Chemical Mixtures Code Number	
ACETONE (CAS 67-64-1)	6532
METHYL ETHYL KETONE (CAS 78-93-3)	6714
TOLUENE (CAS 108-88-3)	594

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)
ACETONE (CAS 67-64-1)
BUTYL BENZYL PHTHALATE (CAS 85-68-7)
ETHYLBENZENE(CAS 100-41-4)
METHYL ETHYL KETONE (CAS 78-93-3)
N-BUTANE (CAS 106-97-8)
TITANIUM DIOXIDE (CAS 13463-67-7)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)
ACETONE (CAS 67-64-1)
BUTYL BENZYL PHTHALATE (CAS 85-68-7)
ETHYLBENZENE (CAS 100- 41-4)
METHYL ETHYL KETONE (CAS 78-93-3)
N-BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)
TITANIUM DIOXIDE (CAS 13463-67-7)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)
ACETONE (CAS 67-64-1)
BUTYL BENZYL PHTHALATE (CAS 85-68-7)
ETHYLBENZENE (CAS 100- 41-4)
METHYL ETHYL KETONE (CAS 78-93-3)
N-BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)
TITANIUM DIOXIDE (CAS 13463-67-7)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)
ACETONE (CAS 67-64-1)
BUTYL BENZYL PHTHALATE (CAS 85-68-7)
ETHYLBENZENE (CAS 100- 41-4)
METHYL ETHYL KETONE (CAS 78-93-3)
N-BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)
TITANIUM DIOXIDE (CAS 13463-67-7)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. Rhode Island RTK

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)
ACETONE (CAS 67-64-1)
BUTYL BENZYL PHTHALATE (CAS 85-68-7) ETHYLBENZENE (CAS 100- 41-4)
METHYL ETHYL KETONE (CAS 78-93-3) N-BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CARBON BLACK (CAS 1333-86-4)	Listed: February 21, 2003
ETHYL ALCOHOL (CAS 64-17-5)	Listed: April 29, 2011
	Listed: July 1, 1988
ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)	Listed: October 1, 1988
TITANIUM DIOXIDE (CAS 13463-67-7)	Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)	Listed: June 15, 2001
BUTYL BENZYL PHTHALATE (CAS 85-68-7)	Listed: December 2, 2005
ETHYL ALCOHOL (CAS 64-17-5)	Listed: October 1, 1987
TOLUENE (CAS 108-88-3)	Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

TOLUENE (CAS 108-88-3)	Listed: August 7, 2009
------------------------	------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-09-2015

Version # 01

HMIS® ratings Health: 2*
 Flammability: 4
 Physical hazard: 0

NFPA ratings Health: 2
 Flammability: 4
 Instability: 0

Disclaimer The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.